



8. MAINTENANCE



Does your Handling equipment need a touch-up? TVH offers a wide range of paint products for Handling equipment with a brand-new look. We offer general RAL colours as well as brand-specific paints. Have a look at our paints and paint accessories for Handling equipment. For complete paint jobs use a paint tin of 2,5 l. For small touch-ups we advise spray cans of 400 ml.

8.1. PAINT AND ACCESSORIES

Paint



TOTAL SOURCE®

For Handling equipment with a brand-new look, TVH offers a wide range in paint products. We offer general RAL colours as well as brand-specific paints.

Our TotalSource paint is a one-component modified alkyd paint. This means that the paint is ...

- › Ready to use
- › Adapted to dry faster and cover better
- › Resistant to weather conditions
- › High gloss and has a long-lasting gloss retention
- › Hardening good
- › Easily processable by means of a paint roller, brush or spray gun.

	Colour	REF Spray 400 ml	REF Can 2,5 l
	Blue	165TA3652	140TA8261
	Blue traffic	165TA3653	107TA7396
	Gentian blue	165TA3654	165TA3660
	Grey	165TA3655	136TA1253

	Colour	REF Spray 400 ml	REF Can 2,5 l
	Black	165TA3657	165TA3661
	Red	165TA3658	107TA7285
	Red / orange	165TA3659	105TA4862
	Yellow	165TA3656	107TA7332

Accessories



Fast-drying synthetic thinner

› Contents: 5 l
REF [107TA7394](#)



Cellulose cleaning thinner

› Contents: 5 l
REF [107TA8760](#)



Polyurethane hardener

› Contents: 0,5 l
REF [107TA7391](#)

Notes



Paint rollers

- › Set of 2 pieces
- › Width: 100 mm

REF [136TA1290](#)



Paint roller holder

- › Width roller: 100 mm
- › Total length: 285 mm

REF [136TA1291](#)



Spraymaster

Aerosol pistol

- › For spray cans of 400 and 500 ml
- › Ensures clean hands when applying technical and colour sprays
- › Aerosol not included

REF [107TA7405](#)

TOTAL SOURCE



Spray gun

- › Spray jet: 1,7 mm

REF [107TA7409](#)



Regular maintenance with quality products extends the life of your Handling equipment considerably. Prevent wear by using greases and hydraulic oil and have a look at our range of technical sprays for cleaning, lubrication, anti-corrosion and protection. Some of them are approved for food-processing industries by NSF. We offer the most common sprays and greases at an excellent price/quality ratio under our own brand: TotalSource.

8.2. TECHNICAL SPRAYS AND LUBRICATION

Technical sprays



Brake cleaner

Efficient brake cleaner with high dissolving properties

- > Contents: 500 ml
- > Non-conductive and non-corrosive
- > Powerful spray jet for: drum and disc brakes, brake linings, calipers and shoes
- > Leaves no residue
- > High price/quality ratio

REF [134TA3719](#)

TOTAL SOURCE



Contact cleaner

High-quality spray designed to clean electrical contacts such as switches, batteries, terminals, printed circuit board switches and multiple sockets

- > Contents: 400 ml
- > Non-conductive and non-corrosive
- > High dissolving properties
- > Leaves no residue
- > High price/quality ratio

REF [144TA6119](#)

TOTAL SOURCE



Battery cleaner with acid indicator

Spray to eliminate and prevent corrosion

- > Contents: 400 ml
- > With acid indicator
- > Turns pink in the presence of acid
- > High price/quality ratio

REF [107TA7662](#)

TOTAL SOURCE



Penetrating oil

Effective tool to loosen rusted parts

- > Contents: 400 ml
- > Moisture-repellent and rust-preventing
- > Good penetrating properties
- > High price/quality ratio

REF [105TA4646](#)

TOTAL SOURCE



White grease

Grease to lubricate mechanical parts made of metal or plastic

- > Contents: 400 ml
- > Multifunctional grease
- > Water-repellent
- > PH-neutral
- > Resistant to weather influences and weak acids and bases
- > High price/quality ratio

REF [107TA8448](#)

TOTAL SOURCE



Inox Klean

Water-based, foaming cleaner for degreasing and cleaning shiny metal surfaces

- > Contents: 500 ml
- > NSF: A7 and C1 - Reg. No. 138083
- > High cleaning power
- > Durable protective coating
- > Suitable for aluminium, stainless steel, chrome and most plastics

REF [143TA6896](#)



Galva Brite

Protective, final coating with a shiny aluminium look

- > Contents: 500 ml
- > Single-component zinc-aluminium coating
- > Resists rusting, peeling and fading
- > Combines corrosion protection properties with a glossy aluminium look
- > Unique combination of flexibility and hardness
- > Totally free of lead and chromates

REF [143TA6911](#)



Galva shine

Touch-up paint for freshly galvanised pieces

- > Contents: 500 ml
- > Protective coating with an exceptional gloss
- > Gives the workpiece the aspect of a freshly hot galvanised piece
- > The film is very resistant and keep its lustre over time
- > Can also be used to give pieces a new zinc look

REF [143TA6912](#)





Food grease

Long-term lubrication for food-processing equipment, where incidental food contact may occur

- › Contents: 500 ml
- › NSF H1 - Reg n° 139016
- › Protects against corrosion
- › Good thermal stability with an operating temperature up to 140 °C

REF [143TA6908](#)



Service set CRC

- › Maintenance set
- › Contents: 4 x 500 ml

REF [165TA1254](#)

Contains:

REF [143TA6909](#) – High speed chain oil

REF [143TA6905](#) – White lithium grease

REF [143TA6901](#) – 5-56 + PTFE

REF [143TA6895](#) – Industrial degreaser



Brakleen Pro

Powerful brake parts cleaner

- › Contents: 500 ml
- › Removes oil, brake fluid, grease, street dirt and other hardened deposits
- › Safe on most rubbers, plastics and coatings
- › Fast-drying
- › Leaves no residue

REF [143TA3579](#)



Label Off Super

Removes self-adhesive paper labels from most surfaces

- › Contents: 400 ml
- › NSF: K3 - Reg n° 139426
- › Test on plastics prior to use
- › Fast-acting: label is ready to be removed 2-3 minutes after spraying

REF [143TA6897](#)



Smartstraw WD-40

Multifunctional spray (cleans, lubricates and protects)

- › Contents: 450 ml
- › Loosens and frees stuck, frozen or rusted metal parts
- › Protects metal surfaces against corrosion
- › Eliminates squeaking
- › Displaces moisture
- › Lubricates (pen oil)
- › User-friendly

REF [142TA8197](#)



Only available in Benelux, Germany, Austria, Switzerland and France

Greases & accessories



Multipurpose grease

Multipurpose grease suitable for a wide range of applications

- > Contents: 400 g
- > Lithium EP2 grease
- > Durable
- > NLGI grade 2
- > Operating temperature: -20 up to 160 °C

REF [165TA3769](#)



Multifunctional grease

- > Contents: 400 g
- > Lical EP2
- > Operating temperature: -20 up to 130 °C

REF [165TA7509](#)



Nevastane XS80

Extreme-pressure, water-resistant, high-temperature calcium sulfonate complex grease for food and food related industries

- > Contents: 400 g
- > NLGI grade 2
- > Approved by NSF as a lubricant for incidental food contact: H1
- > Heavy-duty
- > Operating temperature: -55 up to 180 °C

REF [152TA1875](#)



Foodshield Plus 2

- > Contents: 380 g
- > NLGI grade 2
- > Approved by NSF as a lubricant for incidental food contact: H1
- > Operating temperature: -40 up to 160 °C

REF [165TA7510](#)



Industrial grease gun

- > Designed to be used under rough conditions, with variable stroke system
- > Sealing system that prevents grease compressed in the grease gun from feeding back
- > Capacity: 500 cc or 400 g cartridge DIN 1284
- > M10 x 1
- > 1 high-pressure hose: 11 x 300 mm
- > 1 angled spout
- > 2 precision-machined hydraulic couplers
- > 4 jaws

REF [138TA6594](#)



Oils & accessories



Equivis ZS hydraulic oil

Product description:

- › Recommended for all kinds of hydraulic systems operating under high pressure (limit as indicated by the pump manufacturer) and high temperature (up to 100 °C in hot spots)
- › Lubricants especially suitable for hydraulic systems working under extreme temperature variations and equipment operating outside: easy start-up at low temperatures (-30 °C)

International specifications:

- › Afnor NF E 48-603 HV
- › ISO 6743/4 HV
- › DIN 51524 P3 HVLP
- › Cincinnati Milacron P68, P69, P70
- › Vickers M-2950S, -I-286

Advantages:

- › Very high viscosity index
- › Excellent shear stability
- › Superior thermal stability avoiding the formation of sludge even at high temperatures
- › Very low pour point
- › Good compatibility with elastomers and seals
- › Excellent water and oil demulsification properties
- › Excellent anti-foaming (silicone-free), anti-corrosion and anti-oxidation properties

REF [107TA7212](#) – 5 l, ISO VG 15

REF [141TA3190](#) – 20 l, ISO VG 15

REF [141TA5202](#) – 20 l, ISO VG 22

REF [141TA2734](#) – 20 l, ISO VG 32



Nevastane SH hydraulic oil

Product description:

- › Hydraulic oil recommended in the food-processing industries for the lubrication of hydraulic systems especially operating at low temperatures

International specifications:

- › Complies with the FDA chapter 21 CFR, 178.3570
- › ISO 21469
- › ISO 6743 – 4 HV
- › NSF: H1
- › Recommended for use where incidental food contact is possible
- › Kosher and halal

REF [165TA7513](#) – 20 l, SH 32

REF [165TA7514](#) – 20 l, SH 46

REF [144TA7200](#) – 20 l, SH 68



Equivis XLT hydraulic oil

Product description:

- › A hydraulic fluid designed for outdoor equipment operating under extremely low temperatures
- › The very high viscosity index extends the temperature operating window of the hydraulic systems

International specifications:

- › ISO 11158 HV
- › DIN 51524-3 HVLP

Advantages:

- › The low pour point and low-temperature fluidity limit cavitation issues during start-up operations. Thanks to this low-temperature fluidity, the hydraulic system is fully operable immediately after start-up
- › Good shear stability ensuring a high-temperature lubricating film thickness and hydraulic pump efficiency during the fluid service life
- › Ashless formulation offering a very high oxidation stability, reducing deposits, formation of varnish and allowing extended drain intervals
- › Good wear, rust and corrosion protection of the material
- › Excellent air release behaviour

REF [140TA8776](#) – 20 l, ISO VG 15

REF [165TA7511](#) – 20 l, ISO VG 22

REF [165TA7512](#) – 20 l, ISO VG 32



Standard oiler

Robust brass pump provides trickle feed supply

- › Capacity: 500 ml
- › Steel container and brass pump
- › Ball valve type
- › Delivered with rigid aluminium spout 135 mm and additional flexible spout 210 mm

REF [107TA7253](#)



Oil pump

Universal transfer pump for oil and diesel fuel oil

- › Telescopic shank for drums of 20 to 220 l
- › Delivery capacity: ± 30 l/min

REF [107TA7254](#)